

MODEL : A

300 LB. WWP UL/FM APPROVED

DESCRIPTION

Angle hose valve for Fire protection service,
 Used with a Fire Hose Rack Assembly, or
 as a Fire Hydrant. Outlet connection.

DOUBLE FEMALE

Female NPT inlet and outlet. 300 psi. rated.
 Cast brass valve with red hand wheel.

FEMALE x MALE


Female NPT inlet and Male NPT. 300 lb. rated.
 Cast brass valve with red hand wheel.

The globe pattern is the most reliable and
 acceptable valve to service in wet piping system,
 the primary function of hose valve of hose
 valve with angle type to control the water at the
 hose station.




DIMENSIONS

Size	A (cm)	B (cm)	C (cm) Closed	C (cm) Open	D (cm)	E (cm)	Wt. (Lbs.)
1 1/2"	5.7	5.7	16.5	19	8.9	5	5
2 1/2"	8.9	8.9	24.1	29.1	12.7	6.9	12



Double Female



Female x Male

***QUICK COUPLING ADAPTOR
WITH CAP & CHAIN FOR
ANGLE HOSE VALVE***



MATERIAL	:	CAST BRASS
CONNECTION	:	NH THREADED
SIZE	:	1 1/2", 2 1/2"